



DT-191A

Temperature and Humidity Data Logger

The CEM DT-191A, Plug-PDF Temperature / Humidity datalogger can monitor temperature and humidity values efficiently and conveniently for long. The readings are saved in the logger and simply read out by your PC with USB interface. The innovative tamper proof USB flash disk PDF report generation feature makes it a very reliable tool for accurate Temperature and Humidity measurement and datalogging. Simply plug in the device into any USB and the device generates a PDF report of the untampered data. For more in-depth analysis of the data, like graphing, etc. you can use the analysis software provided.

FEATURES

- Temperature and humidity datalogger
- Instantaneous untampered PDF report on plugin to USB
- Freely selectable sample rate 1 min to 24h
- Clear Large LCD Display of Current / MAX / MIN Temperature and Humidity readings
- Easy USB interface with software for in-depth analysis
- Long Battery life up to 1 year (1 minute sample rate)
- Alarm display if user-defend maximum / minimum value is exceeded
- Robust analysis software for graph view of logged data and data export

SPECIFICATIONS

- Temp. Range : -40 to 70°C / -40 to 158°F
- Temp. Accuracy : $\pm(1^{\circ}\text{C} / 1.8^{\circ}\text{F})$
- Temp. Resolution : $0.1^{\circ}\text{C} / 0.1^{\circ}\text{F}$
- Humidity Range : 0 to 100%RH
- Humidity Accuracy : $\pm 3.5\% \text{RH}$
- Humidity Resolution : $0.1\% \text{RH}$
- Memory : 40020(20010 per channel)
- Sample Rate : User selectable from 1 min to 24 hours interval
- Battery Life : 1year (Sample rate 1 minute)
- PDF Report : Immediately USB flash disk PDF report
- Analysis Software : Windows XP / Vista / win7 / win8 / win10



Tamper proof
data download
in PDF format
Just connect to a computer
no software needed

OR



Download data in
Excel format using
provided software

General Information

Device Information

Model: DT-191A(T+RH) Serial ID: 191A_17041100001
Owner: Logger ID: 0001

Data Logger Setting


Record Start Condition: Start upon keypress Start Time: 02-25-2019 14:53:57
Sampling Rate: 25Sec Stop Time: 02-26-2019 02:00:55
Data Count: 20010 Recorded Time: 11Hours,9Min,56Sec

Alarm Status

Alarm: Enable

Graph

Temperature: Minimum 26.7°C Maximum 31.5°C
Relative Humidity: 41.3%RH 79.3%RH



DT-191A .pdf

Version: V1.0.0.170228

Signature

Accessories : 3V Lithium battery, Analysis Software and Clamshell

Size (HxWxD) : 75mm x 35mm x 16mm

Weight : 50g

Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170

Tel: 0-3844-6117 Fax: 0-3844-6200 Email: info@ete.co.th

www.ete.co.th