

# C65/C66/T75/T76

## Pocket-size Waterproof Conductivity & TDS testers with replaceable probe and manual calibration

Waterproof testers designed for all applications. Their waterproof casing and replaceable probe make them suitable also for heavy duty applications, such as wastewater treatment and agriculture. The modular design allows easy probe and battery replacement.

Specifications	C65	C66	T75	T76
				
<b>Range</b>	0 to 1999 µS/cm	0.00 to 10.00 mS/cm	0 to 1999 ppm (mg/L)	0 to 9990 ppm (mg/L)
<b>Resolution</b>	1 µS/cm	0.01 mS/cm	1 ppm (mg/L)	10 ppm (mg/L)
<b>Accuracy</b>	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
<b>Typical EMC Deviation</b>	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
<b>Temp. Compensation</b>	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C
<b>TDS Factor</b>			0.5	0.5
<b>Calibration</b>	manual at 1 point	manual at 1 point	manual at 1 point	manual at 1 point
<b>Probe</b>	MA73075 (replaceable)	MA73076 (replaceable)	MA73075 (replaceable)	MA73076 (replaceable)
<b>Environment</b>	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%
<b>Battery Type</b>	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline
<b>Battery Life</b>	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use
<b>Packaging dimensions</b>	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm
<b>Packaging weight</b>	157 g	156 g	157 g	156 g

### Accessories

**MA73075** Replaceable conductivity probe, LR  
**MA73076** Replaceable conductivity probe, HR  
**M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)  
**M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs  
**M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs

**M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)  
**M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)  
**M10080B** 800 ppm calib sachet (25 pc)  
**MA753** Hard carrying



### Ordering Information






All testers are supplied in a carton box complete with calibration solution, batteries, instruction manual and screwdriver for calibration.

Optionally **C65**, **C66**, **T75** and **T76** is also available in a kit (**Mi5165**, **Mi5166**, **Mi5175**, **Mi5176**) together with **pH51** pH Meter.



## CD600/CD601/CD610/CD611/CD97 EC & TDS Economical Pocket Testers

Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable EC or TDS values. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions. All EC/TDS testers compensate for the temperature variance automatically.

Specifications	CD600	CD601	CD610	CD611	CD97
					
<b>Range</b>	0 to 1990 ppm	0 to 1990 µS/cm	0 to 10000 ppm	0 to 20000 µS/cm	0 to 1000 ppm
<b>Resolution</b>	10 ppm	10 µS/cm	100 ppm	100 µS/cm	1 ppm
<b>Accuracy</b>	±2% Full scale	±2% Full scale	±2% Full scale	±2% Full scale	±10 ppm
<b>Calibration</b>	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point
<b>Temp. Comp.</b>	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C
<b>Environment</b>	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
<b>Battery Type</b>	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline
<b>Battery Life</b>	350 hours of use	350 hours of use	350 hours of use	350 hours of use	350 hours of use
<b>Packaging dim.</b>	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm
<b>Packaging weight</b>	120 g	120 g	120 g	120 g	120 g



### Accessories

**M10030B** 12880 µS/cm calibration solution, 20 mL (25 pcs)  
**M10031B** 1413 µS/cm calibration solution, 20 mL (25 pcs)  
**M10032B** 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)

**M10038B** 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)  
**MA9015** Electrode storage solution, 230 mL  
**MA9016** Electrode cleaning solution, 230 mL

### Ordering Information

**CD600**, **CD601**, **CD610**, **CD611** and **CD97** are supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.

### Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170

Tel: 0-3844-6200 Fax: 0-3844-6205

Email: info@ete.co.th



www.ete.co.th